



 **MANDA**

LED Catalogue
May 2019

Slim, Light-weight, High-powered LED Light Panels



Made from the next generation of LED beads technology, which reduces energy consumption, while at the same time produces high luminence, these new Vpad and Rpad panels are ideal for most applications in video and photography.

With built-in battery compartments, either V-mount or NP-F types, these panels can be easily deployed outdoors.

	Rpad-112	Rpad-450	Rpad-450V	Rpad-450D	Rpad-450DV
LED	112	256	256	256	256
Power Source	NP-F	NP-F/AC	NP-F/AC/ V-lock	NP-F/AC	NP-F/AC/ V-lock
Max Output	12W	75W	75W	75W	75W
CRI	95%	95%	95%	95%	95%
Color Temp.	3200K-5600K (bi-color)	5600K	5600K	3200K-5600K (bi-color)	3200K-5600K (bi-color)
Size (mm)	ø160 x 28	ø450 x 55	ø450 x 55	ø450 x 55	ø450 x 55
Weight (g)	270	2,000	2,000	2,000	2,000



	Vpad-112	Vpad-150	Vpad-350	Vpad-350D
LED	112	144	350	350
Power Source	NP-F	NP-F	NP-F / AC	NP-F / AC
Max Output	12W	15W	45W	45W
CRI	95%	95%	95%	95%
Color Temp.	3200K-5600K (bi-color)	3200K-5600K (bi-color)	5600K	3200K-5600K (bi-color)
Size (mm)	175 x 167 x 27	288 x 148 x 28	250 x 350	250 x 350
Weight (g)	250	360	1,100	1,100

LED Strip Light Kit



ST-800CB

The ST/ST-C series LED strip light comprises of high quality LED chips/beads, housed in a long and slim panel with built-in diffusion that softens the light.

Setting up is easy and fast because it is light-weight and small in size. The strip panel can be rotated at any angle via its flexible mounting rod.

The ST series of LED strip lights are single-color panel for use as main/key light and/or secondary lighting.

The ST-C series of LED strip lights are multi-color panel — red, yellow, green, indigo, blue, purple and white. The colors can be changed manually by turning the control knob, or automatically. The control knob also functions as a dimmer.

Each kit comes with a light stand, a ball head, goose neck for flexible mounting and an AC Adapter, all inside a bag.


Both panels are available in 2 versions - with and without barn doors.

Specifications:

Model	ST-800	ST-1200	ST-800C	ST-1200C
Max output	55W	70W	40W	55W
Power adapter	15V/4A	15V/5A	15V/3A	15V/4A
CRI	≥95%	≥95%	≥95%	≥95%
Illumination@1m	1100Lx	1300Lx	520Lx	1040Lx
Beam angle	90°	90°	90°	90°
Color temperature	5500±200K	5500±200K	5600±200K	5600±200K
Dimension (mm)	75 x 46 x 855	75 x 46 x 1245	75 x 46 x 855	75 x 46 x 1245
Weight (kg)	1.7	2.3	1.7	2.3




ST-1200



MANDA

HB-48/48S Flexible Bi-Color LED Mat



HB-48S
CAP-shape LED beads

HB-48
flat-shape LED beads

Specifications	HB-48	HB-48S
Output	45W (3200K=45W / 5600K=45W)	
Power	AC 110-240V, 14.8V	
Color temperature	3200-5600K	
CRI	96-98	
Average lifetime	50,000 hrs	
Operating temperature	-15°C to 50°C	
Illumination	1800Lux/1m	3000Lux/1m
LED beads type	Flat shape	CAP shape
LED beads quantity	120 pcs	192 pcs
Beam angle	≥120°	≥60°
Waterproofing rating	IP6	(NA)
Measurement	34 x 34 cm	
Weight	270g	



2.4GHz wireless remote
syncs up to 32 LED mats



softbox attachment



X-mount bracket +
flexible holder




bi-color 3200-5600K

For all enquiries, please email us at info@manda-hk.com



Flexible LED Panel

HB-120S



Light, portable, bendable

Power	120w
Power input	AC100~240v, DC24V/5A
Luminous	11,000Lm
CRI	95
Illumination angle	approx. 120°
Color temp.	3200K~5700K bi-color
Operating temp.	-40°C~85°C
Dimension / weight	540x360mm / 680g
Package	LED, diffuser, detachable frame, tilting adapter, remote, power adapter, bag

IP rating

IP 65

dust proof/water resistant

Wireless Remote

Control up to 4 groupings




Bi-color 3200K to 5700K



Operating Temp.

-40°C to 85°C



Mounting

Detachable frame (portrait/landscape) & tilting adapter



LED SPOTLIGHT HL SERIES

Since it was first introduced the HL Series of LED Spotlight has been a favourite to many for its size, weight and power that a small package has to offer.

The range has been expanded to include versions with power up to 80W. Bowens-mount adapter built-in. Optional remote control for convenience and quick control of the dimmer.

The latest release is the RGB LED Spotlight. A total of 9 RGB variations and a 3200K/5600K color temperature, the HL-180RGB is a versatile LED light for any setup and situation.

Model	HL-300C	HL-400C	HL-600C	HL-800C
Power	30W	40W	60W	80W
Power source	AC110-240V 50-60Hz			
Color temp.	5600K			
Focusing angle	10-40°			
CRI	>90			
Dimension	125 x 125 x 146 mm			
Weight	580 g			

HL-180RGB	
Power	2x18W + 3x12W
Power Source	AC110-240V 50-60Hz
Color Temp.	Bi-color 3200-5600 + RGB full color
Focusing Angle	10-40°
CRI	>90
Dimension	125 x 125 x 146 mm
Weight	580 g



Globe diffuser

These are just some of the Bowens-mount accessories that can be attached to the HL series LED Lights.



Snoot



Optical snoot with gobo



Back Light Reflector



Standard Reflector



Diffuser



1. Switch ON/OFF
2. Dimmer
3. LCD Indicator of Brightness/Battery Volume
4. AC Adapter 100-240V
5. Battery (NP-F series)
6. Bowens-mount adapter
7. Focusing ring



MV-50


LED Spotlight Kit Set

The NEW MV-50 LED Spotlight Kit set comprises of everything you need in a compact, lightweight package. The LED Spotlight is a very bright high CRI LED bulb that emits power at 50W. It is dimmable, runs on both AC adapter (included) or 2 pcs of NP-F batteries (optional).

Sets up in minutes, good to go in any location for use in photography or video. Apply the included barn door or fresnel for a more directional lighting, or use it as flood lighting.

Specifications:

- Power 50W
- Dimmer 0-100%
- Color temp. 5500K
- CRI ≥95
- Lux@1m 1100Lux
- Beam angle 60°
- Battery..... NP-F series x 2
- Adapter 15V / 4A



Light Stand
 Folded length: 490mm
 Full length: 1700mm
 Wt: 1,100g



MV-50 Light Head
 Size: ø95mm x 120mm
 Wt: 500g



25° Fresnel Lens
 Size: ø95mm x 55mm
 Wt: 100g



Barn Door
 Size: ø95mm
 Wt: 100g



AC Adapter
 Size: 115mm x 60mm x 35mm
 Wt: 300g




Ball Head
 Size: 30mm x 100mm
 Wt: 200g

Bag
 Size: 540x260x120mm
 Wt (full package): 3.4kg

For all enquiries, please email us at info@manda-hk.com


LED Ring Lights



RL-60 LED Macro Ring Light

Output power 3.5W
 Power input AAA battery x 3 pcs / DC 3V, 1.2A
 CRI 85%
 Color temp 5600K
 Size 140 x 120 x 30 mm
 Weight 125 g (without batteries)

Comes with 7 adapter rings:
 52 | 55 | 58 | 62 | 67 | 72 | 77 mm



RL-12


RL-12 II

	RL-12	RL-12 II
Output	42W	30W
Power	120-220V, 50/60HZ	120-220V, 50/60HZ
Color Temp.	5500K	3200K - 5600K (bi-color)
CRI	85%	96%
Size	Outer: 345mm Inner: 225mm	Outer: 345mm Inner: 265mm
Weight	1.2kg	0.8kg
Package	Filters (Warm, Diffuse), AC Adapter, Bag	AC Adapter, Bag



RL-18

	RL-18	RL-18 II/RL-18 IIB
Output	55W	55W
Power	120-220V, 50/60HZ	100-220V, 50/60HZ
Color Temp.	5500K	3200K - 5600K (bi-color)
CRI	85%	96%
Size	Outer: 485mm Inner: 365mm	Outer: 445mm Inner: 330mm
Weight	1.6kg	1.2kg
Package	Filters (Warm, Diffuse, Milky), AC Adapter, Bag	AC Adapter, Bag



RL-18 II/RL-18 IIB

RL-18 II – AC only
 RL-18 IIB – AC and DC
 (NF-S type battery)

High Power LED Lights



Small, light weight and very portable. The EL-600 series of high power LED lights are ideal for on-location or studio set-up. With 60W of power in a small form factor, it emits a very bright light that stays cool even after prolong period of use.



	EL-600	EL-600L	EL-600B
Output power	60W	60W	60W
Power input	AC 90-240V, 50/60Hz	AC 90-240V, 50/60Hz	AC 90-240V, 50/60Hz Li-ion Battery 37V, 4mAh
Illumination	6,000Lm	5,000Lm	6,000Lm
CRI	85%	85%	85%
Color temp	5,500K	3,200K	5500K
Size	136 x 127 x 100 mm	136 x 127 x 100 mm	136 x 127 x 100 mm
Weight	1.5 kg	1.5 kg	1.5 kg



Not much bigger than the EL-600 series, the EL-1000 series packs more power for an even stronger light. Bowens-mount compatible accessories such as softboxes, barn doors and many others can be used to shape light as required. Remote control (sold separately) can be used to dim the lights with built-in receiver.

	EL-1000	EL-1000N	EL-1000NL	EL-1000NB
Output power	100W	100W	100W	100W
Power input	AC 90-240V, 50/60Hz	AC 90-240V, 50/60Hz	AC 90-240V, 50/60Hz	AC 90-240V, 50/60Hz V-mount plate only
Illumination	10,000Lm	10,000Lm	8,000Lm	10,000Lm
CRI	85%	85%	85%	85%
Color temp	5,500K	5,500K	3,200K	5500K
Size	390 x 140 x 200 mm	390 x 140 x 200 mm	390 x 140 x 200 mm	390 x 140 x 200 mm
Weight	2.7 kg	2.7 kg	2.7 kg	2.7kg
Built-in 2.4G receiver	NO	YES	YES	YES



For all enquiries, please email us at info@manda-hk.com

